SUPERPAVE ASPHALT MIXTURE DESIGN, WEARING COURSE, PG 64S-22, 3 TO < 30 MILLION ESALS, 9.5 MM MIX, 1.5" DEPTH, MATCH EXISTING SRL OR GREATER SUPERPAVE ASPHALT MIXTURE DESIGN, BINDER COURSE, PG 64S-22, 3 TO < 30 MILLION ESALS, 19.0 MM MIX, 2.5" DEPTH SUPERPAVE ASPHALT MIXTURE DESIGN, BASE COURSE, PG 64S-22, 3 TO < 30 MILLION ESALS, 25.0 MM MIX, 5" DEPTH

2A OR 2RC AS SPECIFIED.

1' SAW CUT. TYP.

- 1. EXPOSED VERTICAL AND HORIZONTAL SURFACES SHALL BE PREPARED AS PER PUB. 408, SECTION 413.3(q).
- 2. MINIMUM 1' PAVEMENT CUTBACK, EXCAVATE OLD AND TEMPORARY MATERIAL RECOMPACT SUB-GRADE. TACK COAT ALL VERTICAL EDGES. INSTALL ONLY BASE COURSE AND BINDER COURSE IN ONE DAY, OR AS
- PERMANENT RESTORATION TO BE MINIMUM 90 DAYS UNLESS FLOWABLE FILL IS USED, OR AS DIRECTED.
  - 1. MATCH EXISTING DEPTHS IF GREATER.
  - 2. RESTORE PAVEMENT MARKINGS WITH APPROVED THERMOPLASTIC

**REVISED 7/20/22** 

PREPARED FOR: PERKASIE REGIONAL AUTHORITY

HOT SEAL ALL EDGES

W/12" WIDE PG 64S-22-

**ASSOCIATES** INCORPORATED

150 RIDGE ROAD, SUITE 2, SKILLERSVILLE, PA 18960 (215) 257-5711

DSN BY: P.C.A. CHK BY: P.C.A DATE: 5/21/12 DWG NO. PRA-S022B